



## XTREME ACCESSORIES

### UNDER CONCRETE SLAB VAPOR BARRIER

#### MASTER FORMAT #033000 - VAPOR BARRIER



### XTREME THIN TAPE

#### DESCRIPTION

Tex-Trude Xtreme Tape is composed of a 7.5 mil thick strong self-adhering rubber based adhesive that has a high tack for a secure bond and is designed to seal the seams of the Xtreme Vapor Barrier Systems. It is also used to seal penetrations coming through the slab, small repairs, and patch areas.



#### INSTALLATION

Prior to installation, perform a visual inspection of the Xtreme Vapor Barrier to insure a 6" overlap has been achieved and all dust, dirt, debris, moisture has been removed.

*Slab Penetration:* Using Xtreme Vapor Barrier material, cut out a minimum of 12" and one-half times the pipe circumference. Cut slits in the boot half the width of the film. Slide the boot over the penetration. The boot is to be in flat contact with the Xtreme Vapor Barrier. It is important to tape the boot to the pipe and around the base.



P.O. BOX 58 CHANNELVIEW, TEXAS 77530  
O. 281.452.5961 F. 281.452.5642 [WWW.TEX-TRUEDE.COM](http://WWW.TEX-TRUEDE.COM)  
©TEX-TRUEDE 2016 ISO 9001-2015



MADE IN THE U.S.A.

*Warm conditions:* Store out of direct sunlight. Perform normal installation, using industry knowledge of the guidelines for vapor barriers.

*Cold conditions:* In cold weather applications, it is suggested to condition the tape 8 hours in a warm environment prior to use. This will help the tape reach its optimal performance.

Note: Only use Xtreme Tapes to seal seams, edges, and penetrations.

## TECHNICAL DATA

Technical Data Xtreme Thin Tape		Packaging Xtreme Thin Tape	
Thickness	7.5 mil	Size	4"x 180'
Permeance	0.112	Rolls Per Case	12
Tensile Strength	25 lbs/in	Weight	4 lb. ea.
Elongation	85%	Weight Per Case	48 lbs
Adhesion	75 oz/in	Color	Red
Cold Weather Resistance	Excellent		
Application Temperature	30F to 160F		
Recommended Storage Conditions	60°F-80°F		

## LIMITED WARRANTY

Tex-Trude warrants this product to meet the published specifications and to be free of defects in workmanship and materials at the time of shipment from our factory. If any Xtreme material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to Xtreme products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.



P.O. BOX 58 CHANNELVIEW, TEXAS 77530  
O. 281.452.5961 F. 281.452.5642 WWW.TEX-TRUEDE.COM  
©TEX-TRUEDE 2016 ISO 9001-2015



MADE IN THE U.S.A.